

## **2022 Street Stock Mini Van/Mini Truck/SUV Rules**

**Any American-made 1980's & newer, V6 or smaller, mini vans, mini trucks, and SUVs ONLY. No hearses or limos are permitted.**

### **General Rules**

1. Read all rules carefully and follow them! Any questions call Tony Godwin 260-223-8956 or Zach Campbell 419-545-4166. There will be no stretching or bending of any rules or you will either run in the modified class or go home!
2. You must pass inspection within 3 times through or you will not be permitted to run.
3. A 12" x 12" roof sign is mandatory. It cannot strengthen the car in anyway.
4. Cars must be stock unless modifications are stated in the rules. Cars must have functioning brakes at all times on at least one axle. No painting of the frames, inside of body of the car, or underneath of the car and inside of the trunk.
5. A helmet, seat belt, and eye protection must be worn at all times on the track.
6. If it doesn't say you can do it, don't do it.
7. Any controversies or protests must be brought up during the drivers meeting. We have the right to reinspect, cut, or drill any car at any time. If you are caught breaking the rules you will forfeit all winnings and/or prizes you are due. If you stretch a rule, you will lose that rule.
8. All airbags, glass, plastic, and interior must be removed before arriving to the event.
9. Any aftermarket parts must be approved. You must call and submit pictures for approval. Parts that are not approved before the derby are not permitted to run.
10. No painting of the frames, inside of the body of the car, or underneath of the car and inside of the trunk. This includes overspray. If found with paint within those areas, the car will not even be inspected.
11. All trailer hitches and braces must be removed.
12. Batteries must be moved to the passenger front floorboard. They must be properly secured and covered.
13. Patching and rust repair will be permitted only if cleared by an official.
14. Officials' decisions are final! All cars are subjected to re-inspection at any time.
15. If the car is found to have plate on the frame or body that the rules do not allow the car will not be permitted to run. There will be no option to fix this problem.
16. If you hammer/shape/weld on the frame in any manner not covered in the rules you will not be able to run. There is no fixing this.

17. You have 1 minute to make an aggressive hit. After 1 minute that car is disqualified. That is 1-minute total. An aggressive hit is solely at the discretion of the officials
18. You are not permitted to hit anyone in the driver's door. If you do, you are disqualified. If you use your driver's door to take advantage of this rule, the car that hit you is not disqualified.
19. You may not get out of your car for any reason during the heat until you are out.
20. You are only permitted to have 1 fire in your car. This will result in a disqualification.
21. No sandbagging, teaming, or holding. Any of these will result in a disqualification. You cannot pin to win.

### **BUILD**

1. Must be 100% stock! No cross breeding of the entire drive. It must be the same make as the car (Ex: Chevy to Chevy, Ford to Ford, etc.) and must appear to be the factory engine to the car. Headers are permitted. The engine must be mounted with stock mounts in the stock position. No welding of the mounts is permitted. They must be bolted only.
2. No homemade cross members are permitted. Cross members must be stock and bolted in, not welded.
3. The doors must be chained or wired in no more than 8 places per door. The wire from the bottom of the doors may go around the frame. You may use 5/6" chain or two strands of #9 wire per hole.
4. The trunks must be chained or wired in no more than 8 places. Two of these may go around the bumper and/or the frame. You are not required to have a deck lid and/or tailgate. No welding or adding metal is permitted. The trunk lid must be in the stock location. No tucking, wedging, pre bending, smashing, folding, or anything else you can think of is permitted. No welding washers for holes is permitted.
5. Hoods may be wired or chained in 8 spots. You may use 5/16" chain or two strands of #9 wire per hole. It must be sheet metal to sheet metal only. No welding washers for holes is permitted. There must be a 12" hole in the hood in case of fire. You must remove the hood latch. Hoods must be open for inspection.
6. Any tires are permitted. Doubled tires are permitted. No foam filled tires are permitted. Valve stem protectors are permitted.
7. You may leave the stock gas tank in the stock location, or you may relocate the fuel tank to the rear floor of the car. If the frame is rusted out, you must relocate the boat tank or aftermarket gas tank. If this is done you must use a fuel cell or boat tank. If you relocate the fuel tank you have 2 options:
  - a. If permitted a back bar, you can have a gas tank holder no bigger than 24" x 24" and it must be 6" away from sheet metal.
  - b. If no back bar is present, you are permitted to have a 24" x 24" x 12" gas tank structure no thicker than 1/4" and it must be bolted to sheet metal only.

8. No stock fuel tanks inside of the car is permitted.
9. The windshield may be left in the car or you can remove the windshield.
10. Creasing on the body from the back doors back is permitted.
11. Stock type springs and shocks are permitted. No solid suspension. Screw in spring risers are permitted. No wire, chains, or any welding on the rear ends or rear spring pockets. Cars must bounce and cars must be stock.
12. You must use the factory rear end for the car you are running.
13. You may weld the spider gears in the rear end to make it posi. No gears are permitted, and you must use stock axles. You are not permitted to change the gear ratio or use aftermarket axles. This will be the driver's responsibility to prove they are not changed.
14. Any car bumper is permitted except for Chrysler pointy bumpers. They must be bolted and welded on in the factory location. You may collapse the shocks and weld all the way around the shock and to the mounting plate to the bumper and there must be an 1½" gap between the frame and the factory bumper shock plate. You can use 4" x 4" box tubing that is 1/4" thick as a bumper that is no more than 5 feet long with no point. The ends of the bumper must remain open. No metal added to the bumper is permitted. If the car has no shocks, the bumper may be welded directly to the frame with no metal added. On the back side of the bumper where the shock mounts you may use a 1/4" x 6" x 6" piece of flat metal to create a flat mounting surface. DEC bumpers and Adept Products bumpers are permitted. Homemade bumpers must be bolted together, not seam welded.
15. If the car has a wiring harness in front of the core support, you may move it behind the core support.
16. All body bolts must be factory stock. No altering is permitted.